

# Stainless Steel W3 ASFA S (12 mm) Hose Clamp - Black

W3



This clamp is manufactured in AISI 430 with an additional matt-black surface treatment which increases its corrosion resistance.

Thanks to the surface treatment, this clamp can be mounted discreetly in any application, making it a favourite in automotive or motorcycle applications. The geometry, band, stamping, housing and screw are identical to other ASFA clamps, meaning that the performance is not altered in any way.

DIN 3017. The Black ASFA SW3 hose clip complies fully with the DIN 3017 norm, and also with the directive EU 20027957EC.

**\* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.**

Ø Application	Part Number	A +0.3 -0.2	L +1 -0.5	S ±0.1	H Max.	B Max.	Maximum values		Box Quantity	Outer Box Quantity
							Pressure (Bar)	Par (Nm)		
16-27	73016206	12	29,6	0,8	11	16,7	45	5,0	50	800
20-32	73016214	12	29,6	0,8	11	16,7	45	6,0	50	800
25-40	73016222	12	29,6	0,8	11	16,7	40	6,0	50	800
30-45	73016230	12	29,6	0,8	11	16,7	35	6,0	50	800
32-50	73016249	12	29,6	0,8	11	16,7	35	6,5	50	800
40-60	73016257	12	29,6	0,8	11	16,7	30	6,5	50	800
50-70	73016265	12	29,6	0,8	11	16,7	25	7,5	50	800
60-80	73016273	12	29,6	0,8	11	16,7	20	7,5	50	400
70-90	73016281	12	29,6	0,8	11	16,7	17	7,5	50	100
80-100	73016290	12	29,6	0,8	11	16,7	14	7,5	25	100
90-110	73016302	12	29,6	0,8	11	16,7	12	7,5	25	400
100-120	73016310	12	29,6	0,8	11	16,7	10	7,5	25	50
110-130	73016329	12	29,6	0,8	11	16,7	8	7,5	25	200
120-140	73016337	12	29,6	0,8	11	16,7	7	7,5	25	200
130-150	73016345	12	31,6	0,8	11	16,7	6	7,5	25	25
140-160	73016353	12	31,6	0,8	11	16,7	6	7,5	25	200
150-170	73016361	12	31,6	0,8	11	16,7	6	7,5	25	25
160-180	73016379	12	31,6	0,8	11	16,7	3	7,5	10	25
170-190	73016387	12	31,6	0,8	11	16,7	3	7,5	10	25
180-200	73016396	12	31,6	0,8	11	16,7	2	7,5	10	25

**\* It is recommended to apply 75% of the maximum values contained in the table.**

TECHNICAL INFORMATION	
<b>MATERIAL</b>	STAINLESS STEEL BAND AND HOUSING W3 AISI 430 X6Cr17 (DIN 1.4016) STAINLESS STEEL W4 AISI 304 Cu SCREW
<b>FINISH</b>	DELTA SEAL BLACK
<b>CORROSION RESISTANCE</b>	250 HOURS SALT SPRAY (ASTM B-117)
<b>MAXIMUM TIGHTENING SPEED (RPM)</b>	540 ± 5

