

Stainless Steel Inner-Ring for ASFA L 9 mm Hose Clamps



This inner-ring for the ASFA L worm-drive clip with 9 mm bandwidth was designed to give extra protection to the hose, especially where it comes into contact with the underside of the clamp housing.

Inner-rings are particularly recommended for use with silicone hoses, which are quite fragile and can be cut easily. The inner-ring ensures a good fit, prevents damage to the hose and also contributes to an even distribution of pressure around the hose.

Ø D Application	Part Number Stainless steel	Part Number black	A ±2	B Max.	C ±0.15	Box Quantity	Outer Box Quantity
16-27	03031034	73031031	3	14,5	12,7	100	800
20-32	03031042	73031040	3	14,5	12,7	100	400
25-40	03031050	73031058	3	14,5	12,7	100	400
30-45	03031069	73031066	3	14,5	12,7	100	100
32-50	03031077	73031074	3	14,5	12,7	100	100
40-60	03031085	73031082	3	15,5	12,7	100	100
50-70	03031093	73031090	3	15,5	12,7	100	100
60-80	03031106	73031103	3	15,5	12,7	100	100
70-90	03031114	73031111	3	15,5	12,7	50	50
80-100	03031122	73031120	3	16,5	12,7	50	50
90-110	03031130	73031138	3	16,5	12,7	25	25
100-120	03031149	73031146	3	16,5	12,7	25	25
110-130	03031157	73031154	3	16,5	12,7	25	25
120-140	03031165	73031162	3	16,5	12,7	25	25
130-150	03031173	73031170	3	16,5	12,7	25	25
140-160	03031181	73031189	3	16,5	12,7	25	25

TECHNICAL INFORMATION		
	MATERIAL	STAINLESS STEEL W4 AISI 301 STAINLESS STEEL W4 AISI 301
	FINISH	BLACK / STAINLESS STEEL
	CORROSION RESISTANCE	400 HOURS SALT SPRAY ASTM B-117
	MAX. TIGHTENING SPEED (RPM)	540 ± 5

