

Stainless Steel Cable Tie




W4

The self-locking mechanism of the cable tie incorporates a stainless-steel ball-bearing making it extremely secure once fastened. Due to its design, the stainless-steel cable tie is tamper-proof once it has been mounted.

Two different bandwidths are available, meaning that you can clamp up to 114kg, and in applications up to 300mm in diameter.

Assembly is carried out using a tool which tightens the tie to its limit and then cuts off the remaining material at the base of the housing, leaving no extra material protruding.

Nominal Measurements	Part Number	Ø Max. Application	a ±0.2	L ±5	S ±0.02	W1 ±0.2	L1 ±0.5	H ±0.2	Resistance (N)	Box Quantity	Outer Box Quantity
4,6 x 39	03002001	39	4,6	129	0,25	6,55	11,00	4,40	890	100	8.000
4,6 x 61	03002002	61	4,6	200	0,25	6,55	11,00	4,40	890	100	6.000
4,6 x 93	03002003	93	4,6	300	0,25	6,55	11,00	4,40	890	100	5.000
4,6 x 116	03002004	116	4,6	370	0,25	6,55	11,00	4,40	890	100	4.000
4,6 x 163	03002005	163	4,6	520	0,25	6,55	11,00	4,40	890	100	4.500
4,6 x 214	03002006	214	4,6	680	0,25	6,55	11,00	4,40	890	100	2.000
4,6 x 265	03002007	265	4,6	840	0,25	6,55	11,00	4,40	890	100	1.000
7,9 x 60	03002008	60	7,9	197	0,25	11,00	13,00	5,25	1.600	100	4.500
7,9 x 93	03002009	93	7,9	300	0,25	11,00	13,00	5,25	1.600	100	4.000
7,9 x 115	03002010	115	7,9	368	0,25	11,00	13,00	5,25	1.600	100	3.000
7,9 x 141	03002011	141	7,9	450	0,25	11,00	13,00	5,25	1.600	100	2.000
7,9 x 157	03002012	157	7,9	500	0,25	11,00	13,00	5,25	1.600	100	2.000
7,9 x 214	03002013	214	7,9	680	0,25	11,00	13,00	5,25	1.600	100	2.000
7,9 x 323	03002014	323	7,9	1.020	0,25	11,00	13,00	5,25	1.600	100	500

	TECHNICAL INFORMATION	
	MATERIAL	W4 AISI 304 STAINLESS STEEL
	FINISH	STAINLESS STEEL
	CORROSION RESISTANCE	400 HOURS SALT SPRAY (ASTM B-117)

