



W1

Wire Clip with Screw

This clip was specially designed for use with hoses incorporating an outer helix. It is generally used when installing ventilation ducting or in white goods applications.

The double-wire construction of this clip means that it sits comfortably on either side of the helix and can then be clamped down firmly thanks to the screw-tightening system.

*** Diameters up 100mm can be manufactured on request.**

Ø Application	Part Number	Ø Optimum application mm	D	d	C	e	L	h mm	Box Quantity	Outer Box Quantity
9,5-12,0	03030015	9,5	M3	1,5	6	5,5	20	11,3	500	2.000
10,5-13,0	03030023	10,5	M3	1,5	6	5,5	20	11,3	500	2.000
11,5-14,0	03030031	11,5	M3	1,5	6	5,5	20	11,3	500	2.000
12,5-15,0	03030040	12,5	M3	1,5	6	5,5	20	11,3	500	2.000
14,0-16,0	03030058	14,0	M3	1,8	6	5,5	25	11,3	500	2.000
14,5-17,0	03030066	14,5	M3	1,8	6	5,5	25	11,3	500	4.000
16,0-18,0	03030074	16,0	M3	1,8	6	5,5	25	11,3	500	2.000
16,5-19,0	03030082	16,5	M3	1,8	6	5,5	25	11,3	500	2.000
18,0-20,0	03030090	18,0	M3	1,8	6	5,5	25	11,3	500	2.000
18,5-21,0	03030103	18,5	M3	1,8	6	5,5	25	11,3	500	500
18,5-22,0	03030111	18,5	M3	2,0	7	7,0	30	14,3	500	500
19,0-23,0	03030120	19,0	M4	2,0	7	7,0	30	14,3	500	500
20,0-24,0	03030138	20,0	M4	2,0	7	7,0	30	14,3	500	500
21,5-25,0	03030146	21,5	M4	2,2	7	7,0	30	14,3	500	500
23,5-27,0	03030154	23,5	M4	2,2	7	7,0	30	14,3	500	500
25,0-29,0	03030162	25,0	M4	2,2	7	7,0	30	14,3	200	800
27,0-31,0	03030170	27,0	M4	2,2	7	7,0	30	14,3	200	200
29,0-33,0	03030189	29,0	M4	2,2	7	7,0	30	14,3	200	800
30,5-35,0	03030197	30,5	M4	2,2	7	7,0	30	14,3	200	200
33,0-37,0	03030200	33,0	M4	2,2	7	7,0	30	14,3	200	1.600

Wire Clip with Screw



W1

This clip was specially designed for use with hoses incorporating an outer helix. It is generally used when installing ventilation ducting or in white goods applications.

The double-wire construction of this clip means that it sits comfortably on either side of the helix and can then be clamped down firmly thanks to the screw-tightening system.

* Diameters up to 100mm can be manufactured on request.

Ø Application	Part Number	Ø Optimum application mm	D	d	C	e	L	h mm	Box Quantity	Outer Box Quantity
35,5-40,0	03030218	35,5	M4	2,2	7	7,0	30	14,3	200	1.600
38,5-43,0	03030226	38,5	M4	2,2	7	7,0	30	14,3	200	200
41,0-46,0	03030234	41,0	M5	2,5	8	8,0	40	15,3	200	200
43,5-49,0	03030242	43,5	M5	2,5	8	8,0	40	15,3	200	200
46,5-53,0	03030250	46,5	M5	2,5	8	8,0	40	15,3	200	200
50,5-56,0	03030269	50,5	M5	2,5	8	8,0	40	15,3	100	200
53,5-60,0	03030277	53,5	M5	2,5	8	8,0	40	15,3	100	100
56,5-64,0	03030285	56,5	M6	2,8	10	10,0	50	18,6	100	100
60,0-68,0	03030293	60,0	M6	2,8	10	10,0	50	18,6	100	100
64,0-72,0	03030306	64,0	M6	2,8	10	10,0	50	18,6	100	100
68,5-76,0	03030314	68,5	M6	3,0	10	10,0	50	18,6	100	100
72,5-80,0	03030322	72,5	M6	3,0	10	10,0	50	18,6	100	100
76,5-84,0	03030330	76,5	M6	3,0	10	10,0	50	18,6	100	100

TECHNICAL INFORMATION	
MATERIAL	W1 STEEL B-UNI 3823
FINISH	ZINC-PLATED Cr3
CORROSION RESISTANCE	48 HOURS SALT SPRAY (ASTM B-117)

