

"Normal" Mini Clip Blister Pack

The Mikalor "Normal" Mini Clip is also available in a sealed plastic blister pack which guarantees that the product is both well-presented and protected. This packing option is ideal for sales points as it allows for self-service, meaning that the customer can avoid unnecessary waits.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.

"Normal" Miniclip							
Part nº	Article	Application Ø	Width	Maximum values		Units/Blister	Dieter/Deeking
				Torque (Nm)	Pressure (Bars)	Units/Blister	Blister/Packing
B301056-0	"Normal" Miniclip 12-13	12-13	10	1	12,5	6	20
B301058-7	"Normal" Miniclip 14-15	14-15	10	1	12	6	20
B301059-5	"Normal" Miniclip 15-17	15-17	10	1	12	6	20
B301060-8	"Normal" Miniclip 16-18	16-18	10	1	11	6	20
B301063-2	"Normal" Miniclip 20-22	20-22	10	1	10	6	20

^{*} It is recommended to apply 75% of the maximum values contained in the table.

TECHNICAL INFORMATION			
MATERIAL	BAND: STEEL ST3 K32 (EN10215) SCREW: STEEL GRADE 6 NUT: STEEL GRADE 6		
FINISH	GREY-WHITE CR3 ZINC-PLATED		
CORROSION RESISTANCE	72 HOURS SALT SPRAY (ASTM B-117)		



