



ASFA L (9 mm) Hose Clamps in plastic bags

This new presentation was designed for shops with a self-service display area. The customers can see and touch the product before purchase. This format is ideal for customers who need only a small quantity of clamps. All bags are stamped with the Mikalor logo and are easily identifiable.

** The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.*

W1

Application Ø mm	Part nº	a +0,5 a -0,2	Maximum values		Units/bag	Quantity bags/ packing	Box Quantity (units)
			Torque (Nm)	Pressure(Bars)			
8-16	03008753B0	9	3,0	40	5	40	200
12-22	03008761B0	9	3,0	40	5	40	200
16-27	03008770B0	9	3,5	38	5	40	200
20-32	03008788B0	9	3,5	36	5	40	200
25-40	03008796B0	9	4,0	32	5	20	100
30-45	03008809B0	9	4,0	28	5	20	100
32-50	03008817B0	9	4,0	24	5	20	100
40-60	03008825B0	9	4,0	19	5	20	100
50-70	03008833B0	9	4,0	17	5	20	100

** It is recommended to apply 75% of the maximum values contained in the table.*

TECHNICAL INFORMATION	
MATERIAL	BAND AND HOUSING: GALVANIZED STEEL (EN 10292) SCREW: STEEL Qst 36-3(DIN 1.0213)
FINISH	BAND AND HOUSING: GALVANIZED STEEL SCREW: GREY-WHITE Cr3 ZINC-PLATED
CORROSION RESISTANCE	144 HOURS SALT SPRAY (ASTM B-117)
MAXIMUM TIGHTENING SPEED (RPM)	540 ±5

