



## SUPRA Hose Clamps in plastic bags

This new presentation was designed for shops with a self-service display area. The customers can see and touch the product before purchase. This format is ideal for customers who need only a small quantity of clamps. All bags are stamped with the Mikalor logo and are easily identifiable.

\* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.

W2

Application Ø mm	Part nº	a	Maximum values		Units/bag	Quantity bags/ packing	Box Quantity (units)
			Torque (Nm)	Pressure (Bars)			
19-21	03019020B0	18	10	40	2	25	50
23-25	03019047B0	18	10	40	2	25	50
25-27	03019055B0	18	10	40	2	25	50
29-31	03019071B0	20	12	35	2	25	50
31-34	03019080B0	20	12	35	2	25	50
37-40	03019100B0	20	12	35	2	25	50
40-43	03019119B0	20	12	35	2	25	50
43-47	03019127B0	20	12	35	2	25	50
47-51	03019135B0	20	16	30	2	25	50
51-55	03019143B0	20	16	30	2	25	50
55-59	03019151B0	20	16	30	2	25	50
59-63	03019160B0	20	16	30	2	25	50
63-68	03019178B0	20	16	30	2	25	50
68-73	03019186B0	25	30	20	2	25	50

\* It is recommended to apply 75% of the maximum values contained in the table.

TECHNICAL INFORMATION	
<b>MATERIAL</b>	BAND AND BRIDGE: STAINLESS STEEL X6CR17 AISI-430 SCREW: STEEL Qst 34-3 (DIN 1.0213) 8.8 grade steel
<b>FINISH</b>	STAINLESS STEEL
<b>CORROSION RESISTANCE</b>	72 HOURS SALT SPRAY (ASTM B-117)
<b>MAXIMUM TIGHTENING SPEED (RPM)</b>	540 ± 5

