



The self-locking mechanism of the cable tie incorporates a stainless-steel ball-bearing making it extremely secure once fastened. Due to its design, the stainless-steel cable tie is tamper-proof once it has been mounted.

Two different bandwidths are available, meaning that you can clamp up to 114kg, and in applications up to 300mm in diameter.

Assembly is carried out using a tool which tightens the tie to its limit and then cuts off the remaining material at the base of the housing, leaving no extra material protruding.

**MATERIAL:** W4 AISI 304  
Stainless Steel  
**CORROSION RESISTANCE:** 400 hours Salt Spray (ASTM B-117)

Ø Application	Part Number	a ±0.2	L ±5	S ±0.02	Resistance (N)	Box Quantity	Outer Box Quantity
4,60 x 129 x 39	03002001	4,6	129	0,25	890	100	8.000
4,60 x 200 x 61	03002002	4,6	200	0,25	890	100	6.000
4,60 x 300 x 93	03002003	4,6	300	0,25	890	100	5.000
4,60 x 370 x 116	03002004	4,6	370	0,25	890	100	4.000
4,60 x 520 x 163	03002005	4,6	520	0,25	890	100	4.500
4,60 x 680 x 214	03002006	4,6	680	0,25	890	100	2.000
4,60 x 840 x 265	03002007	4,6	840	0,25	890	100	1.000
7,90 x 197 x 60	03002008	7,9	197	0,25	1.600	100	4.500
7,90 x 300 x 93	03002009	7,9	300	0,25	1.600	100	4.000
7,90 x 368 x 115	03002010	7,9	368	0,25	1.600	100	3.000
7,90 x 450 x 141	03002011	7,9	450	0,25	1.600	100	2.000
7,90 x 500 x 157	03002012	7,9	500	0,25	1.600	100	2.000
7,90 x 680 x 214	03002013	7,9	680	0,25	1.600	100	2.000
7,90 x 1020 x 323	03002014	7,9	1.020	0,25	1.600	100	500